

# PowerBoss Armadillo Series Spec Information

## PowerBoss Armadillo 6X



- Cleans 124,080 sq ft per hour
- 53" Sweep path
- 36" Main broom, Proex & wire (std)
- 24" Side broom, poly, retractable
- 10 cu ft Hopper w/ RTR<sup>®</sup> feature
- 60" Multi-level high dump
- 650 lbs hopper load capacity
- Excellent dust control filtration system with 92 sq ft filter surface
- Foot operated brakes
- Hand lever parking brakes
- Hour meter & battery condition meter
- Wet sweep filter by-pass
- Aggressive electric filter shakers
- Hydraulic protection package
- Massive, unitized steel frame
- Battery, Gas or Diesel powered
- PowerClimb™ for extra ground clearance
- Tires: Front (2) 16" solid  
Rear: (1) 16" solid
- Oversized, soft-ride tires eliminates jolts and vibration for component protection
- 1.2 HP electric drive motor
- 1.9 HP electric accessory motor
- 82" Turn radius
- Weight: 2,550 lbs Gas/LP/Dsl
- Battery area: 19.77" x 12.06" x 23.06"
- W x L x H: 53" x 79" x 79.5" with Overhead guard
- W x L x H: 53" x 79" x 53" (standard)

# PowerBoss Armadillo 9X / 9XR



- Cleans 184,800 sq ft
- 62" Sweep path
- 48" Main broom, Proex & wire (std)
- 24" Side broom, poly, retractable with Option to add a 2<sup>nd</sup> side broom
- 22 cu ft hopper with RTR<sup>®</sup> feature
- 60" Multi-level high dump
- 1,500 lbs hopper load capacity
- Excellent dust control filtration system With 120 sq ft filter surface
- Aggressive timed electric filter shakers Includes 2 filters and 2 shakers
- Clogged filter indicator
- Hydraulic brakes
- Hand lever parking brake
- Wet sweep filter bypass
- Radiator: Heavy-duty industrial type
- Shock-mounted hydraulic impeller
- 110" Turn radius
- Auto shutdown (high temp / low oil) standard Gas / LP
- Gasoline, LP or Diesel powered
- Engine PowerSwing<sup>™</sup> standard
- PowerClimb<sup>™</sup> with oversized tires
- PowerFlex<sup>™</sup> suspension optional for 9XR
- Massive, unitized steel frame
- Tires: Front: (2) 18" solid  
Rear: (1) 16" solid
- Oversized, soft-ride tires eliminates jolts and vibration for component protection
- Full instrumentation for all functions
- Gauges for fuel, hour meter, volt meter, oil pressure and temperature
- Air cleaner, 3-stage radial seal
- Weight: 3,500 lbs
- W x L x H: 60" x 105" x 81" with Overhead guard and cab
- W x L x H: 60" x 105" x 53.38" standard
- Hydraulic protection package

# PowerBoss Armadillo 10X



- Cleans 217,800 sq ft
- 72 – 84" Sweep path
- 56" Main broom, Proex & wire, standard
- 26" Side broom, poly, retractable with Option to add a 2<sup>nd</sup> side broom
- 30 cu ft hopper with RTR<sup>®</sup> feature
- 64" Multi-level high dump
- 2,000 lbs hopper load capacity
- Excellent dust control filtration system with 180 sq ft filter surface
- Aggressive timed electric filter shakers Includes 2 filters and 2 shakers
- Clogged filter indicator
- Hydraulic brakes
- Hand lever parking brake
- Massive, unitized steel frame
- Wet sweep filter bypass
- Hydraulic protection package
- 115" Turn radius
- Radiator: Heavy-duty industrial type
- Shock-mounted hydraulic impeller
- Gasoline, LP or Diesel powered
- Engine PowerSwing<sup>™</sup>
- Air cleaner: 3-stage radial seal
- Auto shutdown (high temp / low oil) standard on Gas / LP
- Engine area shielded from exhaust air
- PowerFlex<sup>™</sup> standard for 10XV
- PowerClimb<sup>™</sup> with oversized tires
- Tilt and Power steering
- Oversized, sift-ride tires eliminates jolts and vibration for component protection
- Full instrumentation for all functions
- Gauges for fuel, hour meter, volt meter, oil pressure and temperature
- Spark arresting muffler
- Weight: 4,575 lbs
- W x L x H: 60" x 105" x 81" with overhead guard and cab
- W x L x H: 60" x 105 x 53.38" standard
- Tires: Front: (2) 23" pneumatic  
Rear: (1) 21" pneumatic